



The U-Crane Dynamic is a new generation of our gyrostabilized robotic camera crane systems. It is a remotely operated gyrostabilized minicrane technology that was designed for use on small camera cars, electric carts, process trailers or other small tracking vehicles to be able perform on narrow roads, small sized sets, tunnels, parking garages, bridges.

U-Crane Dynamic is lightweight and compact but powerful enough to go high speed and work in most challenging conditions. It is capable of 360° pan, tilting up and down allowing a wide range of impressively stable, smooth and very dynamic shots. U-Crane Dynamic system is operated via joystick consoles from within a camera car.







SPECS	
Arm length	3,63 m
Lens height	3,42m
Tilt	45°
Pan	360°
Max rotations	+- 3 rotations
Pan speed max	4,5 sec/360 °
Tilt speed max	1,5 sec/45°
Max payload	24kg
Weight with camera max	140 kg
Max.speed	160km/h

U-CRANE DYNAMIC

Incl 12vPower + bnc video for wireless teradek
FLIGHTHEAD MINI 4 GPS, incl:
Max Payload 15 kg
Weight head 27 kg
Zoom motor
Spare zoom motor
Shake generator
Joystick control
Wheels control
Camera power cables
XLR to D-Tap cables
ZERO RAINDEFLECTOR
2,7 kg
Incl power
Incl spare glasses

PORSCHE CAYENNE

MONITORS

2x 17" TV logic monitors
2x 9" High bright TV logic monitors
Incl focus assist and waveform
1x 5" High bright TV logic monitor

PLAYBACK DEVICE

PIX EX-7 incl Harddrive

INTERCOM

Digital wireless Clearcom system

- 5 beltpacks
- 3 earpieces

Speaker

12V & 24V STABILISED CAMERA POWER

36V STABILISED HEAD POWER

MULTIPLE 12V OUTPUTS

MULTIPLE BNC VIDEO OUTPUTS